



DCS & Labelling Worldwide

# 随时随地的标签打印



## HT200e

选购件



电池和充电器



手持扫描枪



笔式扫描枪



PCMCIA卡

## 2英寸独立式直热打印机

SATO的HT200e直热打印机可独立移动操作，无需连接电脑，可随时随地打印标签。配上电力持久的专用锂电池，使HT200e无需固定电源也可以进行标签打印。是零售折扣店里，应对快速周转的商品，即时标签打印的理想选择。



打印方式	直热
打印分辨率	203dpi (8dpmm)
最大打印范围	W48mm x L96mm (W1.89" x L3.78")
打印速度	60 or 80mm/sec (2.4ips or 3.1ips) 使用电池时为60mm/sec
标签类型	卷筒纸, 带黑标的模切纸 2种颜色直热打印—— 黑色/红色
标签尺寸	宽度: 25 ~ 48mm (0.98" ~ 1.89") 底纸尺寸: 28 ~ 51mm (1.1" ~ 2.01") 长度: 13 ~ 100mm (0.51" ~ 3.94") 底纸尺寸: 16 ~ 103mm (0.63" ~ 4.06") 厚度: 0.14 ~ 0.19mm
标签卷尺寸	最大外径: 75mm (2.95") 内径: 26.5mm (1.1") 外卷
感应模式	Reflective sensor for use with pre-printed sensing I-marks
接口选择	数据传输和扫描枪接口: RS-232C
条码	EAN8, EAN13, UPC-A/E, * For the following barcodes, only available at Free mode NW - 7, Inter-leaved 2/5 (ITF), CODE 39, CODE 128 [Subset B (without control codes)/Subset C]
字体	X1: Width 20 x Height 50 Dots (Alphanumeric, Symbol) X2: Width 8 x Height 20 Dots (Alphanumeric, Symbol) X3: Width 13 x Height 21 Dots (Alphanumeric, Symbol) OCR-B: Width 20 x Height 24 Dots (Numeric, English capital letters) Price Font: Width 16 x Height 24 Dots (Numeric, currency mark) POP1: Width 28 x Height 48 Dots (Numeric, currency mark) POP2: Width 48 x Height 68 Dots (Numeric, currency mark) POP3: Width 26 x Height 56 Dots (Numeric, currency mark)
功能	<b>自检功能</b> Cover open, Paper end, Head check, Test print, Battery check Memory backup battery check (Backup battery life is 10 years) PC card battery check (Memory card battery life is 2 years) <b>控制面板按键</b> FNC1, FNC2, FMT, PGUP, RCL, AC, 0~9, SHFT, SET, FEED S/S, ENTR, DEL, DATE, #, \$, !, " <b>LCD</b> Alphanumeric display 16 Characters x 3 Lines with back-light <b>Memory Storage</b> Fixed FMT: 29 Free FMT: 15 Preset Approx. 300 (Internal Memory) Approx. 2000 (Option: 2MB SRAM card memory)
外形尺寸 (打印机)	W132mm x D230mm x H151 mm (W 5.2" x D9.2" x H6")
外形尺寸 (充电器)	W130mm x D117mm x H28mm (W5.2" x D6" x H1.1")
重量	Approx. 2.5kg (Printer with battery installed) Approx. 2.4kg (With Power Supply unit installed) 330g (Adaptor)
电源要求	输入电压: AC 110 / 230V±10% 输出电压和电流: DC8.4V 3.2A Power Consumption: Maximum 71 VA 43W
环境要求	运行: 5 ~ 40°C (41 ~ 104°F) 无凝结, 30 - 80% 存储: -5 ~ 60°C (23 ~ 140°F) 无凝结, 30 - 90%
认证情况	CE Marking, TUV, UL, CSA, CCC
选件	电池, 充电器, PCMCIA卡, 回卷器, Unwinder, Touch/Pen scanner RS-232C Cable, RS-232C Extension cable

## Asia Pacific &amp; Oceania

SATO INTERNATIONAL ASIA PACIFIC PTE. LTD.  
438A, Alexandra Road  
#05-01/04, Alexandra Technopark  
Singapore 119967  
Tel: +65-6271-2122, Fax: +65-6271-2151  
Email: asia@sato-int.com

## SATO SHANGHAI CO., LTD.

佐藤自动识别系统国际贸易(上海)有限公司  
中国上海虹口区海宁路307号爱思大厦10F  
邮编: 200080  
Tel: 86 (021) 6306 8899  
Fax: 86 (021) 6309 1318  
E-mail: sales@satochina.com

## 深圳分公司

地址: 深圳市福田区福华一路98号  
卓越大厦807室  
邮编: 518048  
Tel: 86 (0755) 8344 8631  
Fax: 86 (0755) 8344 8630

## 广州分公司

地址: 广州市天河区珠江新城华强路3-2  
富力盈力大厦北塔2006室  
Tel: 86 (020) 3862 8003  
Fax: 86 (020) 3862 7674